

## FAS PVA High Grade

Revision: Sept 2008

Contact: FAS PH: +64 9 274 8896 FAX: +64 9 274 1091

### IDENTIFICATION

<b>PRODUCT NAME:</b>	FAS PVA Craft Glue High Grade
<b>TRADE NAME:</b>	As Above
<b>OTHER NAMES:</b>	None
<b>USES:</b>	Adhesive
<b>UN NUMBER:</b>	Non-Applicable
<b> DANGEROUS GOODS CLASS &amp; SUBSIDIARY RISK:</b>	Non-Applicable
<b>TOXIC SUSTANCES SCHEDULE:</b>	Not Listed
<b>HAZCHEM CODE:</b>	Non-Hazardous
<b>POISONS SCHEDULE:</b>	Non-Poisonous

### PHYSICAL DESCRIPTION / PROPERTIES

<b>APPEARANCE:</b>	White Milky Liquid
<b>ODOUR:</b>	Slight
<b>COLOUR:</b>	White in liquid form, Clear when dry
<b>VAPOUR PRESSURE:</b>	As Water
<b>SPECIFIC GRAVITY:</b>	1.05 - 1.15
<b>FLAMMABILITY LIMITS(%):</b>	Non-Applicable
<b>pH:</b>	7.0 - 8.5
<b>BOILING POINT (deg C):</b>	100
<b>FLASH POINT (deg C):</b>	Non-Applicable
<b>SOLUBILITY IN WATER:</b>	Infinitely Miscible
<b>INGREDIENTS:</b>	Poly vinyl acetate latex, water.

### HEALTH HAZARD INFORMATION:

#### HEALTH EFFECTS:

<b>SWALLOWED:</b>	Not expected to be harmful.
<b>EYE:</b>	Not expected to cause irritation
<b>SKIN:</b>	Irritation may result upon prolonged contact
<b>INHALED:</b>	Product may contain trace levels of vinyl acetate monomer. Under normal conditions of use the levels are not expected to pose an inhalation risk.

#### FIRST AID:

<b>SWALLOWED:</b>	Rinse mouth. Drink water. Do not induce vomiting. (Do not give liquids to unconscious person)
<b>EYE:</b>	Irrigate with water if accidentally applied to the eye. Seek medical attention if irritation persists.
<b>SKIN</b>	Wash and contamination fresh water.
<b>INHALED:</b>	In the unlikely event that the trace levels of vinyl acetate monomer cause any symptom, remove patient to fresh air and seek medical assistance.

#### ADVICE TO DOCTOR:

Treat symptomatically. Product contains up to 400ppm vinyl acetate monomer.

#### PRECAUTIONS FOR USE

<b>EXPOSURE LIMITS:</b>	TWA vinyl acetate monomer 10 ppm 35mg/cu.m
<b>VENTILATION:</b>	No special precautions under normal use.
<b>PERSONAL PROTECTION:</b>	No special precautions under normal use.
<b>FLAMMABILITY:</b>	Non-Applicable.

#### SAFE HANDLING INFORMATION

<b>STORAGE AND TRANSPORT:</b>	Not regulated.
<b>SPILL AND DISPOSAL:</b>	Wash with water.
<b>FIRE / EXPLOSION HAZARD:</b>	NA LEL: NA UEL: NA
<b>EXTINGUISHING MEDIA:</b>	Non-Applicable.
<b>DECOMPOSITION PRODUCTS:</b>	Non-Applicable
<b>HAZARDOUS POLYMERIZATION / INSTABILITY:</b>	Will not occur.



FAS PVA Craft Glue High Grade dries clear and offer a extra strong bond that is ideal for woodwork and general purpose bonding. Solids of 50%

**Use For:** Suited for a wide range of applications in the classroom activates when using paper, card and for wood construction..

**SIZES:**  
500ml and 2 Litre  
(Pump available separately for 2Ltr)

**Application:** Can be applied directly from the bottle/jar. Surfaces must be clean, dry and free from grease. Apply to only one surface an even coat of glue. Press both surfaces together while still wet. Light clamping may be necessary for some applications for 20-30 minutes. Drying time is complete after 12 hours (depending on weather conditions).

**Clearing:** Dried glue can be removed with warm soapy water. Clean bottle nozzle before replacing cap. To wash out of clothing, use warm water and a laundry detergent. Wash up equipment with soap and water.